

# keyword.txt de base de l'IDE dans dossier \lib

keyword.txt

```
#FUNCTIONS COLOR          #D35400 - ORANGE          KEYWORD1
#FUNCTIONS COLOR          #D35400 - ORANGE          KEYWORD2
#STRUCTURE COLORS        #728E00 - GREEN          KEYWORD3
#VARIABLES COLOR         #00979C - BLUE           LITERAL1

# LITERAL1 specifies constants

HIGH    LITERAL1    Constants    RESERVED_WORD_2
LOW    LITERAL1    Constants    RESERVED_WORD_2
INPUT  LITERAL1    Constants    RESERVED_WORD_2
INPUT_PULLUP    LITERAL1    Constants    RESERVED_WORD_2
OUTPUT LITERAL1    Constants    RESERVED_WORD_2
DEC    LITERAL1    Serial_Print    RESERVED_WORD_2
BIN    LITERAL1    Serial_Print    RESERVED_WORD_2
HEX    LITERAL1    Serial_Print    RESERVED_WORD_2
OCT    LITERAL1    Serial_Print    RESERVED_WORD_2
PI     LITERAL1    RESERVED_WORD_2
HALF_PI LITERAL1    RESERVED_WORD_2
TWO_PI LITERAL1    RESERVED_WORD_2
LSBFIRST    LITERAL1    ShiftOut    RESERVED_WORD_2
MSBFIRST    LITERAL1    ShiftOut    RESERVED_WORD_2
CHANGE     LITERAL1    AttachInterrupt    RESERVED_WORD_2
FALLING    LITERAL1    AttachInterrupt    RESERVED_WORD_2
RISING     LITERAL1    AttachInterrupt    RESERVED_WORD_2
DEFAULT    LITERAL1    AnalogReference    RESERVED_WORD_2
EXTERNAL   LITERAL1    AnalogReference    RESERVED_WORD_2
INTERNAL   LITERAL1    AnalogReference    RESERVED_WORD_2
INTERNAL1V1 LITERAL1    AnalogReference    RESERVED_WORD_2
INTERNAL2V56    LITERAL1    AnalogReference    RESERVED_WORD_2
LED_BUILTIN LITERAL1    Constants    RESERVED_WORD_2
LED_BUILTIN_RX LITERAL1    Constants    RESERVED_WORD_2
LED_BUILTIN_TX LITERAL1    Constants    RESERVED_WORD_2

DIGITAL_MESSAGE LITERAL1    Constants    RESERVED_WORD_2
FIRMATA_STRING  LITERAL1    Constants    RESERVED_WORD_2
ANALOG_MESSAGE  LITERAL1    Constants    RESERVED_WORD_2
REPORT_DIGITAL  LITERAL1    Constants    RESERVED_WORD_2
REPORT_ANALOG   LITERAL1    Constants    RESERVED_WORD_2
SET_PIN_MODE    LITERAL1    Constants    RESERVED_WORD_2
SYSTEM_RESET    LITERAL1    Constants    RESERVED_WORD_2
SYSEX_START     LITERAL1    Constants    RESERVED_WORD_2

auto    LITERAL1    RESERVED_WORD_2
```

```

int8_t LITERAL1 RESERVED_WORD_2
int16_t LITERAL1 RESERVED_WORD_2
int32_t LITERAL1 RESERVED_WORD_2
int64_t LITERAL1 RESERVED_WORD_2
uint8_t LITERAL1 RESERVED_WORD_2
uint16_t LITERAL1 RESERVED_WORD_2
uint32_t LITERAL1 RESERVED_WORD_2
uint64_t LITERAL1 RESERVED_WORD_2

char16_t LITERAL1 RESERVED_WORD_2
char32_t LITERAL1 RESERVED_WORD_2
operator LITERAL1 RESERVED_WORD_2
enum LITERAL1 RESERVED_WORD_2
delete LITERAL1 RESERVED_WORD_2
bool LITERAL1 RESERVED_WORD_2
boolean LITERAL1 BooleanVariables RESERVED_WORD_2
byte LITERAL1 Byte RESERVED_WORD_2
char LITERAL1 Char RESERVED_WORD_2
const LITERAL1 Const RESERVED_WORD_2
false LITERAL1 Constants LITERAL_BOOLEAN
float LITERAL1 Float RESERVED_WORD_2
double LITERAL1 RESERVED_WORD_2
null LITERAL1 RESERVED_WORD_2
NULL LITERAL1 RESERVED_WORD_2
int LITERAL1 Int RESERVED_WORD_2
long LITERAL1 Long RESERVED_WORD_2
new LITERAL1 RESERVED_WORD_2
private LITERAL1 RESERVED_WORD_2
protected LITERAL1 RESERVED_WORD_2
public LITERAL1 RESERVED_WORD_2
short LITERAL1 RESERVED_WORD_2
signed LITERAL1 RESERVED_WORD_2
static LITERAL1 Static RESERVED_WORD_2
volatile LITERAL1 Volatile RESERVED_WORD_2
String LITERAL1 String RESERVED_WORD_2
void LITERAL1 Void RESERVED_WORD_2
true LITERAL1 LITERAL_BOOLEAN
unsigned LITERAL1 RESERVED_WORD_2
word LITERAL1 RESERVED_WORD_2
array LITERAL1 Constants RESERVED_WORD_2
sizeof LITERAL1 Constants RESERVED_WORD_2
dynamic_cast LITERAL1 Constants RESERVED_WORD_2
typedef LITERAL1 Constants RESERVED_WORD_2
const_cast LITERAL1 Constants RESERVED_WORD_2
struct LITERAL1 Constants RESERVED_WORD_2
static_cast LITERAL1 Constants RESERVED_WORD_2
union LITERAL1 Constants RESERVED_WORD_2
friend LITERAL1 Constants RESERVED_WORD_2
extern LITERAL1 Constants RESERVED_WORD_2
class LITERAL1 Constants RESERVED_WORD_2

```

```

reinterpret_cast    LITERAL1    Constants    RESERVED_WORD_2
register            LITERAL1    Constants    RESERVED_WORD_2
explicit           LITERAL1    Constants    RESERVED_WORD_2
inline             LITERAL1    Constants    RESERVED_WORD_2
_Bool              LITERAL1    Constants    RESERVED_WORD_2
complex            LITERAL1    Constants    RESERVED_WORD_2
_Complex           LITERAL1    Constants    RESERVED_WORD_2
_Imaginary         LITERAL1    Constants    RESERVED_WORD_2
atomic_bool        LITERAL1    Constants    RESERVED_WORD_2
atomic_char        LITERAL1    Constants    RESERVED_WORD_2
atomic_schar       LITERAL1    Constants    RESERVED_WORD_2
atomic_uchar       LITERAL1    Constants    RESERVED_WORD_2
atomic_short       LITERAL1    Constants    RESERVED_WORD_2
atomic_ushort      LITERAL1    Constants    RESERVED_WORD_2
atomic_int         LITERAL1    Constants    RESERVED_WORD_2
atomic_uint        LITERAL1    Constants    RESERVED_WORD_2
atomic_long        LITERAL1    Constants    RESERVED_WORD_2
atomic_ulong       LITERAL1    Constants    RESERVED_WORD_2
atomic_llong       LITERAL1    Constants    RESERVED_WORD_2
atomic_ullong      LITERAL1    Constants    RESERVED_WORD_2
virtual            LITERAL1    Constants    RESERVED_WORD_2
PROGMEM           LITERAL1    Constants    RESERVED_WORD_2

```

# KEYWORD2 specifies methods and functions

```

abs KEYWORD2      Abs
acos  KEYWORD2    ACos
acosf  KEYWORD2
asin  KEYWORD2    ASin
asinf  KEYWORD2
atan  KEYWORD2    ATan
atan2  KEYWORD2    ATan2
atan2f KEYWORD2
atanf  KEYWORD2
cbirt  KEYWORD2
cbirtf KEYWORD2
ceil  KEYWORD2    Ceil
ceilf  KEYWORD2
constrain KEYWORD2  Constrain
copysign KEYWORD2
copysignf KEYWORD2
cos KEYWORD2     Cos
cosf  KEYWORD2
cosh  KEYWORD2
coshf KEYWORD2
degrees KEYWORD2
exp KEYWORD2     Exp
expf  KEYWORD2
fabs  KEYWORD2
fabsf KEYWORD2
fdim  KEYWORD2

```

```
fdimf KEYWORD2
floor KEYWORD2      Floor
floorf KEYWORD2
fma KEYWORD2
fmaf KEYWORD2
fmax KEYWORD2
fmaxf KEYWORD2
fmin KEYWORD2
fminf KEYWORD2
fmod KEYWORD2
fmodf KEYWORD2
hypot KEYWORD2
hypotf KEYWORD2
isfinite KEYWORD2
isinf KEYWORD2
isnan KEYWORD2
ldexp KEYWORD2
ldexpf KEYWORD2
log KEYWORD2      Log
log10 KEYWORD2
log10f KEYWORD2
logf KEYWORD2
lrint KEYWORD2
lrintf KEYWORD2
lround KEYWORD2
lroundf KEYWORD2
map KEYWORD2      Map
max KEYWORD2      Max
min KEYWORD2      Min
pow KEYWORD2      Pow
powf KEYWORD2
radians KEYWORD2
random KEYWORD2    Random
randomSeed KEYWORD2 RandomSeed
round KEYWORD2
roundf KEYWORD2
signbit KEYWORD2
sin KEYWORD2      Sin
sinf KEYWORD2
sinh KEYWORD2
sinhf KEYWORD2
sq KEYWORD2      Sq
sqrt KEYWORD2     Sqrt
sqrtf KEYWORD2
tan KEYWORD2      Tan
tanf KEYWORD2
tanh KEYWORD2
tanhf KEYWORD2
trunc KEYWORD2
truncf KEYWORD2
```

```
bitRead KEYWORD2    BitRead
bitWrite    KEYWORD2    BitWrite
bitSet    KEYWORD2    BitSet
bitClear    KEYWORD2    BitClear
bit    KEYWORD2    Bit
highByte    KEYWORD2    HighByte
lowByte    KEYWORD2    LowByte

analogReference KEYWORD2    AnalogReference
analogRead    KEYWORD2    AnalogRead
analogReadResolution    KEYWORD2    AnalogReadResolution
analogWrite    KEYWORD2    AnalogWrite
analogWriteResolution    KEYWORD2    AnalogWriteResolution
attachInterrupt    KEYWORD2    AttachInterrupt
detachInterrupt    KEYWORD2    DetachInterrupt
digitalPinToInterrupt    KEYWORD2    DigitalPinToInterrupt
delay    KEYWORD2    Delay
delayMicroseconds    KEYWORD2    DelayMicroseconds
digitalWrite    KEYWORD2    DigitalWrite
digitalRead    KEYWORD2    DigitalRead
interrupts    KEYWORD2
millis    KEYWORD2    Millis
micros    KEYWORD2    Micros
noInterrupts    KEYWORD2    NoInterrupts
noTone    KEYWORD2    NoTone
pinMode    KEYWORD2    PinMode
pulseIn    KEYWORD2    PulseIn
pulseInLong    KEYWORD2    PulseInLong
shiftIn    KEYWORD2    ShiftIn
shiftOut    KEYWORD2    ShiftOut
tone    KEYWORD2    Tone
yield    KEYWORD2    Yield

Stream    KEYWORD2
Serial    KEYWORD1    Serial    DATA_TYPE
Serial1    KEYWORD1    Serial    DATA_TYPE
Serial2    KEYWORD1    Serial    DATA_TYPE
Serial3    KEYWORD1    Serial    DATA_TYPE
SerialUSB    KEYWORD1    Serial    DATA_TYPE
begin    KEYWORD2    Serial_Begin
end    KEYWORD2    Serial_End
peek    KEYWORD2    Serial_Peek
read    KEYWORD2    Serial_Read
print    KEYWORD2    Serial_Print
println    KEYWORD2    Serial_Println
available    KEYWORD2    Serial_Available
availableForWrite    KEYWORD2
flush    KEYWORD2    Serial_Flush
setTimeout    KEYWORD2
find    KEYWORD2
```

```
findUntil    KEYWORD2
parseInt     KEYWORD2
parseFloat   KEYWORD2
readBytes    KEYWORD2
readBytesUntil KEYWORD2
readString   KEYWORD2
readStringUntil KEYWORD2
trim         KEYWORD2
toUpperCase  KEYWORD2
toLowerCase  KEYWORD2
charAt       KEYWORD2
compareTo    KEYWORD2
concat       KEYWORD2
endsWith     KEYWORD2
startsWith   KEYWORD2
equals       KEYWORD2
equalsIgnoreCase    KEYWORD2
getBytes     KEYWORD2
indexOf      KEYWORD2
lastIndexOf  KEYWORD2
length       KEYWORD2
replace      KEYWORD2
setCharAt    KEYWORD2
substring    KEYWORD2
toCharArray  KEYWORD2
toInt        KEYWORD2

Keyboard     KEYWORD1      DATA_TYPE
Mouse        KEYWORD1      DATA_TYPE
press        KEYWORD2
release      KEYWORD2
releaseAll   KEYWORD2
accept       KEYWORD2
click        KEYWORD2
move         KEYWORD2
isPressed    KEYWORD2

isAlphaNumeric KEYWORD2
isAlpha         KEYWORD2
isAscii         KEYWORD2
isWhitespace    KEYWORD2
isControl       KEYWORD2
isDigit         KEYWORD2
isGraph         KEYWORD2
isLowerCase     KEYWORD2
isPrintable     KEYWORD2
isPunct         KEYWORD2
isSpace         KEYWORD2
isUpperCase     KEYWORD2
isHexadecimalDigit KEYWORD2
```

```
# KEYWORD3 specifies structures

break   KEYWORD3   Break   RESERVED_WORD
case    KEYWORD3   SwitchCase  RESERVED_WORD
override  KEYWORD3   RESERVED_WORD
final   KEYWORD3   RESERVED_WORD
continue KEYWORD3   Continue  RESERVED_WORD
default KEYWORD3   SwitchCase  RESERVED_WORD
do      KEYWORD3   DoWhile   RESERVED_WORD
else    KEYWORD3   Else      RESERVED_WORD
for     KEYWORD3   For       RESERVED_WORD
if      KEYWORD3   If        RESERVED_WORD
return  KEYWORD3   Return   RESERVED_WORD
goto    KEYWORD3   RESERVED_WORD

switch  KEYWORD3   SwitchCase  RESERVED_WORD
throw   KEYWORD3   RESERVED_WORD
try     KEYWORD3   RESERVED_WORD
while   KEYWORD3   While      RESERVED_WORD

setup   KEYWORD3   Setup     RESERVED_WORD
loop    KEYWORD3   Loop      RESERVED_WORD
export  KEYWORD3   RESERVED_WORD

not     KEYWORD3   If        RESERVED_WORD
or      KEYWORD3   If        RESERVED_WORD
and     KEYWORD3   If        RESERVED_WORD
xor     KEYWORD3   If        RESERVED_WORD

# operators aren't highlighted, but may have documentation

+=      IncrementCompound
+       Arithmetic
[]      arrayaccess
=       assign
&       BitwiseAnd
|       BitwiseAnd
^       BitwiseAnd
~       BitwiseXorNot
,
//      Comments
?:
{}      Braces
--      Increment
/       Arithmetic
/*     Comments
.       dot
==      If
<       If
<=     If
```

```
++      Increment
!=      If
<<     Bitshift
>      If
>=     If
&&     Boolean
!      Boolean
||     Boolean
-      Arithmetic
%      Modulo
*      Arithmetic
()     parentheses
>>     Bitshift
;      SemiColon
-=     DecrementCompound

#include  KEYWORD3      PREPROCESSOR
#define  KEYWORD3      PREPROCESSOR
#elif   KEYWORD3      PREPROCESSOR
#else   KEYWORD3      PREPROCESSOR
#error  KEYWORD3      PREPROCESSOR
#if     KEYWORD3      PREPROCESSOR
#ifdef  KEYWORD3      PREPROCESSOR
#ifndef KEYWORD3      PREPROCESSOR
#pragma KEYWORD3      PREPROCESSOR
#warning KEYWORD3      PREPROCESSOR
```

From: <https://www.fablab37110.chanterie37.fr/> - Castel'Lab le Fablab MJC de Château-Renault

Permanent link: <https://www.fablab37110.chanterie37.fr/doku.php?id=start:arduino:ide:keyword&rev=1664443891>

Last update: **2023/01/27 16:08**

